



LED Street Lighting

LSL-C Series: Street and area lighting available in 50W, 100W, 150W and 200W

The LSL-C Series comprises versatile LED lights that deliver high performance street and area lighting. Fitted with driver-on-board technology, these luminaires offer impressive lighting in a compact, weather resistant aluminium chassis.

LSL-C Series lights feature a 180° adjustable pole mount and can be fitted to vertical or angled fittings. They are ideal for illumination in street lighting applications, in area lighting for public spaces and for general purpose lighting in a variety of commercial and industrial building environments.

- Available in 50W, 100W, 150W and 200W models
- High 110lm/W luminous efficacy for energy efficiency
- Long lifespan LED lighting: rated for up to 35,000 hours
- Driver-on-board technology for compact size & affordability
- Slimline, aluminium, IP65 weather rated enclosure
- Adjustable base with 180° of vertical rotation

Series Specifications

Model	LSL-C50-C	LSL-C100-C	L	.SL-C150-C	LSL-C200-C			
Product Image				THE STATE OF THE S	c)			
Series Name		LSL-C Series	LED Street Light:	S				
Optical								
Light Output	5500lm	11000lm		16500lm	22000lm			
Luminous Efficacy			10lm/W					
Colour Temperature			6000K					
Colour Rendering Index	> 80							
Beam Angle		90)° x 130°					
Rated Lifespan		35,0	000 hours					
Electrical								
Power Consumption	50W	100W		150W	200W			
Input Voltage			~ 220VAC					
Power Factor			>0.9					
Dimmable			N/A					
Detection								
Motion Detection			N/A					
On-Time Delay	N/A							
Standby Light Modes			N/A					
General								
Ingress Protection			IP65					
Plug / Socket / Base	Unterminated (H05RN-F 3G0,75mm²)							
Reflector / Diffuser	Polycarbonate lens							
Housing Adjustments	180° adjustable housing							
Pole Installation	Ø54mm (Max.) Ø62.1mm (Max.)							
Housing Construction	Aluminium							
Operating Environment		-20)° ~ 50°C					
Dimensions	440 x 180 x 80mm	550 x 240 x 110mm	590>	c 270 x 110mm	670 x 300 x 90mm			
Photometry								
Max Intensity Distribution (100W Model)	1200 12400 13600 4800 6000 House Side Street S	(100W Mode	ght Distribution I)	90° 75° 60° 45°	90 ~ 270° Units:cd 1200 2400 4800 15° 0° 15° 30°			

Ordering Information

Туре		Series	Wattage	Colour Temperature		
LSL	-	С	50 (50W) 100 (100W) 150 (150W) 200 (200W)	- C (Cool white)		
		LSL-C50-0	: 50W LED street l	light in cool white		

Your local AVOL $^{\scriptscriptstyle\mathsf{TM}}$ lighting solutions professional: